



PLC-335P-AU-IR2/PR

Dome 5MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-335P-AU-IR2/PR

Dome 5MP



Specifications:

Model Name	PLC-335P-AU-IR2/PR
Imaging Device	1/2.7" Progressive CMOS
Scanning System	Progressive Scanning
Min. Illumination	0.05lux@F1.2 (AGC ON),0Lux with IR ON
Video Output	BNC
Resolution	5MP 2592 (H) ×1944 (V)
Max. Framerate	5AHD/5TVI: 5MP@20fps 4AHD/4CVI/4TVI: P@25fps N@30fps CVBS: 960H
Max. Aperture Ratio	F1.6/F2.2
Lens Type/ Focal Length	Fixed lens /2.8mm/3.6mm
Audio	Audio over coaxial
Audio Range	7m
IR Distance	20m
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Video Transmission Distance	MAX 300M (Cable : 5C 2V)
Operating Temperature / Humidity	-30°C ~ 55°C / 90%
Ingress Protection	IP66
Input Voltage/Current	12V DC
Power Consumption	IR OFF ≤ 0.8W, IR ON ≤ 4W
Color / Material	Plastic

Dimensions:

