



PLC-338M-MZ-IR5/PR

Dome 8MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au





PLC-338M-MZ-IR5/PR

Dome 8MP

Specifications:

Model Name	PLC-338M-MZ-IR5/PR
Imaging Device	1/2.7" Progressive CMOS
Scanning System	Progressive Scanning
Min. Illumination	0.05lux@F1.2 (AGC ON),0Lux with IR ON
Video Output	BNC
Resolution	8MP 3840 (H) ×2160 (V)
Max. Framerate	AHD/TVI/CVI: 8MP@15fps, TVI/CVI : 8MP@12.5fps, CVBS: 960H CVBS: 960H
Max. Aperture Ratio	F1.8-3.3
Lens Type/ Focal Length	Motorized lens / 2.8-12mm
IR Distance	50m
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Wide Dynamic Range	D-WDR (Off/On)
Digital Noise Reduction	2D DNR
Gain Control	HIGH
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Video Transmission Distance	MAX 300M (Cable: 5C 2V)
Operating Temperature / Humidity	-30°C ~ 55°C / 90%
Ingress Protection	IP67
Input Voltage/Current	12V DC
Power Consumption	IR OFF ≤ 1W, IR ON ≤ 4W
Color / Material	Metal

Dimensions:

