



PLC-422M-AI-IR3/PR

Bullet 2MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-422M-AI-IR3/PR

Bullet 2MP



Specifications:

Model name	PLC-422M-AI-IR3/PR
Imaging Device	1/2.8"
Effective Pixels	2MP 1920(H)×1080(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.002lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	3.6mm/2.8mm
Max. Aperture Ratio	F No. 1.6
Angular Field of View	Horizontal: 87°, Vertical:44°, Diagonal: 104°
Min. Object Distance	2m
Lens Type	Fixed(M12)
IR Viewable Length	Up to 30m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	PID, LCD, PD/VD, FD, SOD, CC, HM, CD, QD, RSD, LPD
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Mainstream @30fps 1080P(1920x1080), 960P(1280x960), 720P(1280x720) Substeam @30fps 720P(1280x720), VGA(640x480), QVGA(320x240) Mobile stream @30fps VGA(640x480), QVGA (320x242)
Video Quality Adjustment	256Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
IP	IPv6

Streaming Capability	Triple-Stream (Main/Sub/Mobile)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Web browser	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Security Streaming Method	IP address filter; complicated password; Authenticated username and password
Application Programming Interface	ONVIF (Profile S/G/T)
Operating Conditions	-35~+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption (IR OFF)	2W-3W
Power Consumption (IR ON)	4W-5.5W
Material	Metal
Dimensions (H x W x D)	150.8*70.9*70.9mm
Weight	400g

Dimensions:
