



PLC-432M-MZ-AU-IR5/PR

Dome 2MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au





PLC-432M-MZ-AU-IR5/PR

Dome 2MP

Specifications:

Model Name	PLC-432M-MZ-AU-IR5/PR
Imaging Device	1/2.7"
Effective Pixels	2MP 1920(H)×1080(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.006lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	2.8-12mm
Max. Aperture Ratio	F No. 1.8(W) ~ 3.3(T)
Angular Field of View	H:107° (W) -35° (T) V:54° (W) -20° (T) D:133° (W) -40° (T)
Min. Object Distance	1.2m (W/T)
Lens Type	Motorized(Ø14)
IR Viewable Length	Up to 50m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
Mirror	Flip/Rotation
On-Board Storage	Micro SD slot, up to 256GB
Alarm	1 input, 1 output
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream &30fps 1080P(1920x1080) Sub Steam &20fps VGA (640x480)
Video Quality Adjustment	256Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Dual-Stream (Main/Sub)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP

Web browser	IE10/11
Security	IP address filter; complicated password; Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF
Operating Conditions	-35~+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption OFF)	2.5W-3.5W
Power Consumption ON)	6.5W-8.5W
Material	Metal
Dimensions (H x W x D)	135*135*120mm
Weight	846g

Dimensions:
