



PLC-435M-AU-IR3/PR

5MP Dome Camera



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-435M-AU-IR3/PR

5MP Dome Camera



Specifications:

Model	PLC-435M-AU-IR3/PR
Resolution	5MP 2592(H)×1944(V)
Image Sensor	1/2.7" Progressive CMOS
Min. Illumination	Colour 0.05lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Shutter	1/5 ~ 1/20000s
Slow shutter	Support
Lens	Fixed 2.8mm
View Angle	H: 92°, V: 69°
F No.	F No. 1.85±10%
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Schedule)
Digital noise reduction:	3D DNR
WDR	Digital WDR
Video Compression	H.265/H.264
Video bit rate	8Kbps ~ 8Mbps
Dual - Stream	Yes
Resolution	Mainstream (default 15fps/5MP) 5MP(2592×1944), 4MP(2592×1520), 3MP(2048×1520), (2304×1296), 1080P(1920×1080), 960P(1280×960), 720P(1280×720) Sub stream default 10fps/VGA) VGA(640×480), QVGA(320×240)
Image Settings	Flip, Rotation, Saturation, Brightness, Contrast, Hue, Sharpness adjustable
BLC	Support
Privacy Mask	Support
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPoE, SMTP, NTP, UPnP, SNMP, HTTPS, FTP,
System Compatibility	ONVIF(Profile S, Profile G)
Interface	RJ45 10M / 100M Ethernet interface x1
LED	18pcs (SMD)
IR Range	Up to 30m
SD storage	Support up to 128GB
Built-in Microphone	Yes
PoE	Yes
Water Proof	IP 66
Power Supply	DC 12V/POE
Consumption	≤ 9W
Storage Temperature	-30 ~ +60°C
Operating Temperature	-30 ~ +55°C

Dimension:

