



PLC-425M-MZ-AU-IR5/PR

Bullet 5MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-425M-MZ-AU-IR5/PR

Bullet 5MP



Specifications:

| | |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Name | PLC-425M-MZ-AU-IR5/PR |
| Imaging Device | 1/2.7" |
| Effective Pixels | 5MP 2592(H)×1944(V)@30fps |
| Scanning System | Progressive CMOS |
| Min. Illumination | Color 0.004lux @ F1.6(AGC ON); B/W 0 lux @ IR ON |
| Focal Length (Zoom Ratio) | 2.7-13.5mm |
| Max. Aperture Ratio | F No. 1.8 (W) ~ 3.3(T) |
| Angular Field of View | Horizontal: 31 ~102°, Vertical: 23 ~ 73°, Diagonal: 38 ~ 138° |
| Min. Object Distance | 0.3m~INF |
| Lens Type | Manual(Ø14) |
| IR Viewable Length | Up to 50m |
| Camera Title | On/Off |
| Day & Night | IR cut filter with auto switch Day/Night/Auto/Image/Schedule) |
| Backlight Compensation | Off/On (5 Zone) |
| Wide Dynamic Range | DWDR |
| Digital Noise Reduction | 3D DNR |
| Motion Detection | Off/On (8 Level) |
| Privacy Masking | Off/On (4 Zone, Rectangle) |
| Gain Control | Auto |
| White Balance | Auto/Manual |
| Electronic Shutter Speed | 1/5 ~ 1/20000s |
| On-Board Storage | Micro SD slot, up to 256GB |
| Alarm | NA |
| Audio | 1 input (RCA), 1 output (RCA) |
| Hardware Reset | Yes |
| Smart Feature | NA |
| Ethernet | RJ45(10/100BASE-T) |
| Video Compression Format | H.265/H.264 |
| Resolution | Main Stream: 5MP (2592*1944), 4MP (2592x1520), 3MP (2304x1296), @30fps, 1080P(1920x1080) @30fps, 960P(1280x960) @30fps 720P (1280x720) @30fps Sub Steam @20fps 720P(1280x720), VGA (640x480), QVGA (320x240) Mobile Stream @20fps QVGA (320x240) |
| Video Quality Adjustment | 256Kbps ~ 8Mbps |
| Bitrate control method | CBR/VBR |

| | |
|------------------------------------------|--------------------------------------------------------------------------------------------|
| Streaming Capability | Triple-Stream (Main/Sub/Mobile) |
| Protocol | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP |
| Web browser | IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above |
| Security | IP address filter; complicated password; Authenticated username and password |
| Streaming Method | Unicast/Multicast |
| Application Programming Interface | ONVIF (Profile S/G/T) |
| Operating Conditions | -35~+60°C/less than ≤ 95% RH |
| Ingress Protection | IP67 |
| Input Voltage / Current | D12V/POE(IEEE802.3af) |
| Power Consumption OFF) | 2W-3W |
| Power Consumption ON) | 6W-8W |
| Material | Metal |
| Dimensions (H x W x D) | 242*87.4*83.88mm |
| Weight | 782g |

Dimensions:
