



PLC-428M-MZ-IR5/PR

Bullet 8MP



Pollo Pty Ltd.

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: info@pollo.net.au

Website: www.pollo.net.au



PLC-428M-MZ-IR5/PR

Bullet 8MP



Specifications:

Model	PLC-428M-MZ-IR5/PR
Imaging Device	1/2.8"
Effective Pixels	8MP 3840(H)×2160(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.009lux @ F1.6(AGC ON); B/W 0 lux @ IR ON
Focal Length (Zoom Ratio)	2.7-13.5mm
Max. Aperture Ratio	F No. 1.8 (W) ~ 3.3(T)
Angular Field of View	Horizontal: 33 ~111°, Vertical: 18 ~ 57°, Diagonal: 37 ~ 134°
Min. Object Distance	0.8m~INF(W), 1m~INF(T)
Lens Type	Motorized(Ø14)
IR Viewable Length	Up to 50m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	1 input, 1 output
Audio	1 input (RCA), 1 output (RCA)
Hardware Reset	Yes
Smart Feature	Face Detection, Line Crossing & Intrusion Detection
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	Main Stream 30fps 8MP(3840x2160), 5MP(2592x1944,3072x1728), 4MP(2592x1520), 3MP(2304x1296), 1080P(1920x1080), 960P(1280*960), 20P(1280x720), Sub Steam 30fps 1080P(1920x1080), 720P(1280x720), VGA(640x480) Mobile Stream 30fps VGA(640x480), QVGA (320x240)
Video Quality Adjustment	256Kbps ~ 16Mbps
Bitrate control method	CBR/VBR
IP	IPv6

Streaming Capability	Triple-Stream (Main/Sub/Mobile)
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, SMTP, NTP, UPnP, SNMP, HTTPS, FTP
Web browser	IE10/11, Safari V12.1 above, Firefox V.52 above, Google chrome V.57 above, Edge V.79 above
Security Streaming Method	IP address filter; complicated password; Authenticated username and password
Application Programming Interface	ONVIF (Profile S/G/T)
Operating Conditions	-35~+60°C/less than ≤ 95% RH
Ingress Protection	IP67
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption (IR OFF)	3W-4W
Power Consumption (IR ON)	7W-9W
Material	Metal
Dimensions (H x W x D)	242*87.4*83.88mm
Weight	811g

Dimensions:

