



**PLF-20K-VL7**

**Visible Light Indoor  
Facial Recognition**



**Pollo Pty Ltd.**

Address: Suite 401, 55 Phillips St. Parramatta, NSW 2150

Phone: 1300 6600 368

Email: [info@pollo.net.au](mailto:info@pollo.net.au)

Website: [www.pollo.net.au](http://www.pollo.net.au)



## PLF-20K-VL7

### Visible Light Indoor Facial Recognition



#### Features:

Support nighttime fill light with photosensitive sensor coordination.

Support external identity card/IC card reader.

WiFi optional

English as default language, other language customized

Support serial port, Wiegand output, output content support configuration.

Adopt dynamic face detection and tracking recognition algorithm based on video stream.

Recognition speed is fast, it takes about 20ms on face tracking and detection, 300ms on face feature extraction and 1s on face comparison.

Support face recognition scene photo saving.

Support interface docking and support customization.

Support LAN device deployment.

Support screen display content configuration, custom company name and LOGO.

Support for identifying distance configurations.

#### Technical Specification:

<b>Model</b>	<b>PLF-20K-VL7</b>
<b>Recognition</b>	Face, Fingerprint, Card, Pin
<b>CPU</b>	1.5GHZ+1.2Tops
<b>OS</b>	LINUX
<b>Display</b>	7 inch IPS LCD 1024*600
<b>Touch</b>	Capacitive

<b>Camera</b>	200W px Live Detection
<b>RAM</b>	512MB
<b>ROM</b>	8GB
<b>Recognition Time</b>	≤0.2 sec
<b>Users Capacity</b>	20,000
<b>Face Capacity</b>	20,000
<b>Fingerprint Capacity</b>	20,000
<b>Card Type</b>	IC/ID
<b>Card Capacity</b>	20,000
<b>PWD Capacity</b>	20,000
<b>Record Capacity</b>	200,000+200,000(snap)
<b>Attendance Function</b>	U-disk card attendance report/software download attendance report
<b>Recognition Distance</b>	0.5-2 m; Live 0.5-1 m
<b>Access Control Interface</b>	Wiegand 26/34 (input/output), door magnet, electric lock, door opening button, doorbell, RS485
<b>Access Control Limit</b>	42 time period, Anti-PassBack
<b>Access Control Alarm Type</b>	Anti-removal alarm, illegal door opening alarm, door not closed alarm
<b>Communication Method</b>	U-disk / TCP/IP / WiFi
<b>Language</b>	English
<b>Power Supply</b>	Wide Voltage DC12V/5A
<b>Using Scenario</b>	Indoor/Outdoor
<b>Waterproof</b>	IP65
<b>Size</b>	Aluminum alloy 275*135*31mm
<b>Installation</b>	Wall-mounted / Column-mounted